MAY 16 1987

FEM 1.209:390631

FLOOD INSURANCE STUDY

COMPLETED

ORIGINAL

VILLAGE OF STRASBURG, OHIO

TUSCARAWAS COUNTY

AUGUST 4, 1987

Federal Emergency Management Agency

COMMUNITY NUMBER - 390631

BEST COPY AVAILABLE

15

NOTICE TO
FLOOD INSURANCE STUDY USERS

Communities participating in the National Flood Insurance Program (NFIP) have established repositories of flood hazard data for floodplain management and flood insurance purposes. This Flood Insurance Study (FIS) may not contain all data available within the repository. It is advisable to contact the community repository for any additional data.

1 BEST COPY AVAILABLE

TABLE OF CONTENTS

		Page
1.0	INTRODUCTION	1
1.1	Purpose of Study	1
1.2	Authority and Acknowledgments	1
1.3	Coordination	1
2.0	AREA STUDIED	2
2.1	Scope of Study	2
2.2	Community Description	2
2.3	Principal Flood Problems	2
2.4	Flood Protection Measures	2
3.0	ENGINEERING METHODS	2
3.1	Hydrologic Analyses	4
3.2	Hydraulic Analyses	4
4.0	FLOODPLAIN MANAGEMENT APPLICATIONS	5
4.1	Floodplain Boundaries	5
4.2	Floodways	6
5.0	INSURANCE APPLICATION	8
6.0	FLOOD INSURANCE RATE MAP	8
7.0	OTHER STUDIES	9
8.0	LOCATION OF DATA	9
9.0	REFERENCES AND BIBLIOGRAPHY	9

BEST COPY AVAILABLE

TABLE OF CONTENTS (continued)

Page

FIGURES

Figure 1 - Vicinity Map 3

Figure 2 - Floodway Schematic 8

TABLES

Table 1 - Summary of Discharges 4

Table 2 - Floodway Data 7

EXHIBITS

Flood Profiles

Sugar Creek Panel 01P

Flood Insurance Rate Map

Elevation Reference Marks

FLOOD INSURANCE STUDY

VILLAGE OF STRASBURG,
TUSCARAWAS COUNTY,
OHIO

1.0 INTRODUCTION

1.1 Purpose of Study

This Flood Insurance Study investigates the existence and severity of flood hazards in the Village of Strasburg, Tuscarawas County, Ohio, and aids in the administration of the National Flood Insurance Act of 1968 and the Flood Disaster Protection Act of 1973. This study has developed flood risk data for various areas of the community that will be used to establish actuarial flood insurance rates and assist the community in its efforts to promote sound floodplain management. Minimum floodplain management requirements for participation in the National Flood Insurance Program are set forth in the Code of Federal Regulations at 44 CFR, 60.3.

In some states or communities, floodplain management criteria or regulations may exist that are more restrictive or comprehensive than the minimum Federal requirements. In such cases, the more restrictive criteria take precedence and the state (or other jurisdictional agency) will be able to explain them.

This Flood Insurance Study was prepared by compiling existing hydrologic and hydraulic technical and scientific data prepared originally for purposes other than the National Flood Insurance Program. The data were identified as the best available at the time of compilation of this Flood Insurance Study and should depict the general conditions of the flooding sources with relative accuracy. The Federal Emergency Management Agency (FEMA) performed a cursory review and accepted the data as valid for purposes of this Flood Insurance Study and the National Flood Insurance Program. However, if better information is known to exist or has been developed since the date of this report, the information should be immediately forwarded to the Natural and Technological Hazards Division, FEMA, Chicago, Illinois, for consideration for revision of this study.

1.2 Authority and Acknowledgments

The sources of authority for this Flood Insurance Study are the National Flood Insurance Act of 1968 and the Flood Disaster Protection Act of 1973.

The hydrologic and hydraulic analyses for this study were obtained from a report entitled, "Flood Plain Management Study Sugar Creek, South Fork of Sugar Creek, Brandywine Creek and Broad Run, Tuscarawas County, Ohio" (Reference 1).

1.3 Coordination

On September 2, 1986, the results of this Flood Insurance Study were reviewed and accepted at a final coordination meeting attended by representatives of the community and FEMA.

BEST COPY AVAILABLE

2.0 AREA STUDIED

2.1 Scope of Study

This Flood Insurance Study covers the incorporated area of the Village of Strasburg, Tuscarawas County, Ohio. The area of study is shown on the Vicinity Map (Figure 1).

The areas studied by detailed methods were selected based on the extent and validity of available existing hydrologic and hydraulic data.

Flooding caused by overflow of Sugar Creek was studied in detail within the community.

2.2 Community Description

The Village of Strasburg is located in northwestern Tuscarawas County, Ohio, and is surrounded by the unincorporated areas of the county. Tuscarawas County is located in eastern Ohio approximately 15 miles south of the City of Canton. The community is serviced by Interstate 77 and U.S. Route 250. The 1980 population of the community was reported to be 2,091 (Reference 2).

The soils in the study area reflect their glacial origins. Well-drained Huntington soils occupy the floodplains and are underlain by silty, alluvial material. Well-drained Wheeling and well-drained droughty Chillean soils occupy alluviated terraces that are underlain by stratified gravelly and sandy material. Terraces are level to gently sloping.

A continental climate pervades the study area with air masses from northwest and central Canada much of the year and warm, tropical air from the Gulf of Mexico during the summer months. Precipitation totals 40 inches per year with the heaviest rainfall occurring in the early spring (Reference 3).

2.3 Principal Flood Problems

Due to the parameters of this existing data study, information regarding flooding problems in the community is obtained only from the source reports (References 1 and 4) and any other readily available sources. None of these sources provided information relating to the flooding problems in the community.

2.4 Flood Protection Measures

The Beach City Dam is one of fourteen flood control reservoirs constructed in the Muskingum River basin by the U.S. Army Corps of Engineers (COE). This project provides a high degree of protection against flooding along Sugar Creek through the community of Strasburg.

BEST COPY AVAILABLE



FIGURE 1

FEDERAL EMERGENCY MANAGEMENT AGENCY

VILLAGE OF STRASBURG, OH

(TUSCARAWAS CO.)

APPROXIMATE SCALE

4 0 4 8 12 MILES

VICINITY MAP

BEST COPY AVAILABLE

3.0 ENGINEERING METHODS

For the flooding sources studied in detail in the community, standard hydrologic and hydraulic study methods were used to determine the flood hazard data required for this study. Flood events of a magnitude that are expected to be equaled or exceeded once on the average during any 10-, 50-, 100-, or 500-year period (recurrence interval) have been selected as having special significance for floodplain management and for flood insurance rates. These events, commonly termed the 10-, 50-, 100-, and 500-year floods, have a 10-, 2-, 1-, and 0.2-percent chance, respectively, of being equaled or exceeded during any year. Although the recurrence interval represents the long-term average period between floods of a specific magnitude, rare floods could occur at short intervals or even within the same year. The risk of experiencing a rare flood increases when periods greater than 1 year are considered. For example, the risk of having a flood that equals or exceeds the 100-year flood (1-percent chance of annual exceedence) in any 50-year period is approximately 40 percent (4 in 10), and, for any 90-year period, the risk increases to approximately 60 percent (6 in 10). The analyses reported herein reflect flooding potentials based on conditions existing in the community at the time of completion of this study. Maps and flood elevations will be amended periodically to reflect future changes.

3.1 Hydrologic Analyses

Hydrologic analyses were carried out to establish the peak discharge-frequency relationships for each riverine flooding source studied in detail affecting the community.

Natural discharge-frequency curves used in this study were developed on a regional basis in accordance with the method outlined in "Statistical Methods in Hydrology" (Reference 5).

Discharges for Sugar Creek were obtained from the COE stream gages at Beach City Dam and Strasburg.

Peak discharge-drainage area relationships for the 10-, 50-, and 100-year floods of each flooding source studied in detail in the community are shown in Table 1.

TABLE 1 - SUMMARY OF DISCHARGES

FLOODING SOURCE AND LOCATION	DRAINAGE AREA (SQ MILES)	PEAK DISCHARGE (CFS)		
		10-YEAR	50-YEAR	100-YEAR
SUGAR CREEK				
11.36 miles above mouth	300	2,400	2,600	4,290

3.2 Hydraulic Analyses

Analyses of the hydraulic characteristics of flooding from the sources studied were carried out to provide estimates of the elevations of floods of the selected recurrence intervals.

BEST COPY AVAILABLE

Cross-section data for streams were obtained from field surveys, which included the channel and a nominal distance across the overbank. The remaining overbank data were taken from topographic maps (Reference 6). In addition, all bridges within the study reach were field surveyed.

Channel and overbank roughness factors (Manning's "n") used in the hydraulic computations were based on field observations of the stream and floodplain area. The values used for Sugar Creek ranged from 0.037 to 0.043 for the channel and from 0.040 to 0.100 for the overbank areas.

Locations of selected cross sections used in the hydraulic analyses are shown on the Flood Profiles. For stream segments for which a floodway was computed (Section 4.2), selected cross-section locations are also shown on the Flood Insurance Rate Map.

Starting water-surface elevations were developed using established ratings at the Strasburg gaging station. Water-surface profiles of floods of the selected recurrence intervals for Sugar Creek were computed using the U.S. Soil Conservation Service water-surface profile program, WSP-2 (Reference 7).

Flood profiles were drawn showing the computed water-surface elevations for floods of the selected recurrence intervals. In cases where the 50- and 100-year flood elevations are close together, due to limitations of the profile scale, only the 100-year profile has been shown.

The hydraulic analyses for this study are based only on the effects of unobstructed flow. The flood elevations shown on the profiles are thus considered valid only if hydraulic structures remain unobstructed, operate properly, and do not fail.

All elevations are referenced to the National Geodetic Vertical Datum of 1929 (NGVD). Elevation reference marks used in this study are shown on the map and described in the exhibit labeled Elevation Reference Marks.

4.0 FLOODPLAIN MANAGEMENT APPLICATIONS

The National Flood Insurance Program encourages state and local governments to adopt sound floodplain management programs. Therefore, each Flood Insurance Study provides 100-year flood elevations and delineations of the 100- and 500-year floodplain boundaries and 100-year floodway to assist communities in developing floodplain management measures.

4.1 Floodplain Boundaries

To provide a national standard without regional discrimination, the 1-percent annual chance (100-year) flood has been adopted by FEMA as the base flood for floodplain management purposes. The 0.2-percent annual chance (500-year) flood is employed to indicate additional areas of flood risk in the community. For each stream studied in detail, the 100- and 500-year floodplain boundaries have been delineated using the flood elevations determined at each cross section. Between cross sections, the boundaries were interpolated using topographic maps at a scale of 1:24000 with a contour interval of 20 feet (Reference 6).

BEST COPY AVAILABLE

The 100- and 500-year floodplain boundaries are shown on the Flood Insurance Rate Map. On this map, the 100-year floodplain boundary corresponds to the boundary of the areas of special flood hazards (Zones A, AE, AH, AO, A99, V, and VE) and the 500-year floodplain boundary corresponds to the boundary of areas of moderate flood hazards. In cases where the 100- and 500-year floodplain boundaries are close together, only the 100-year floodplain boundary has been shown. Small areas within the floodplain boundaries may lie above the flood elevations but cannot be shown due to limitations of the map scale and/or lack of detailed topographic data.

4.2 Floodways

Encroachment on floodplains, such as structures and fill, reduces the flood-carrying capacity, increases the flood heights and velocities, and increases flood hazards in areas beyond the encroachment itself. One aspect of floodplain management involves balancing the economic gain from floodplain development against the resulting increase in flood hazard. For purposes of the National Flood Insurance Program, a floodway is used as a tool to assist local communities in this aspect of floodplain management. Under this concept, the area of the 100-year floodplain is divided into a floodway and a floodway fringe. The floodway is the channel of a stream plus any adjacent floodplain areas that must be kept free of encroachment so that the 100-year flood can be carried without substantial increases in flood heights. Minimum Federal standards limit such increases to 1.0 foot, provided that hazardous velocities are not produced. The floodways in this study are presented to local agencies as minimum standards that can be adopted directly or that can be used as a basis for additional floodway studies.

The floodways presented in this study were computed for certain stream segments on the basis of equal conveyance reduction from each side of the floodplain. Floodway widths were computed at cross sections. Between cross sections, the floodway boundaries were interpolated. The results of the floodway computations are tabulated for selected cross sections and are shown in Table 2, Floodway Data. The computed floodways are shown on the Flood Insurance Rate Map. In cases where the floodway and the 100-year floodplain boundaries are either close together or collinear, only the floodway boundary is shown. Portions of the floodway for Sugar Creek lie outside the corporate limits.

The area between the floodway and the 100-year floodplain boundaries is termed the floodway fringe. The floodway fringe encompasses the portion of the floodplain that could be completely obstructed without increasing the water-surface elevation of the 100-year flood more than 1.0 foot at any point. Typical relationships between the floodway and the floodway fringe and their significance to floodplain development are shown in Figure 2.

BEST COPY AVAILABLE

FLOODING SOURCE		FLOODWAY			BASE FLOOD WATER SURFACE ELEVATION			
CROSS SECTION	DISTANCE[1]	WIDTH (FEET)	SECTION AREA (SQ. FEET)	MEAN VELOCITY (FEET/SEC.)	REGULATORY (FEET NGVD)	WITHOUT FLOODWAY (FEET NGVD)	WITH FLOODWAY (FEET NGVD)	INCREASE (FEET)
SUGAR CREEK								
A	42,007	88	710	6.0	913.2	913.2	914.2	1.0
B	45,778	518[2]	3369	1.3	919.8	919.8	920.8	1.0

[1]FEET ABOVE MOUTH
[2]THIS WIDTH EXTENDS BEYOND CORPORATE LIMITS

BEST COPY AVAILABLE

TABLE 2

FEDERAL EMERGENCY MANAGEMENT AGENCY

VILLAGE OF STRASBURG, OH

(TUSCARAWAS CO.)

FLOODWAY DATA

SUGAR CREEK


100-YEAR FLOOD PLAIN
FLOODWAY FRINGE
FLOODWAY
FLOODWAY FRINGE
STREAM CHANNEL
FLOOD ELEVATION WHEN CONFINED WITHIN FLOODWAY
ENCROACHMENT
ENCROACHMENT
C
D
SURCHARGE *
A
B
AREA OF FLOOD PLAIN THAT COULD BE USED FOR DEVELOPMENT BY RAISING GROUND
FLOOD ELEVATION BEFORE ENCROACHMENT ON FLOOD PLAIN
LINE AB IS THE FLOOD ELEVATION BEFORE ENCROACHMENT.
LINE CD IS THE FLOOD ELEVATION AFTER ENCROACHMENT.
*SURCHARGE IS NOT TO EXCEED 1.0 FOOT (FEMA REQUIREMENT) OR LESSER AMOUNT IF SPECIFIED BY STATE.

FIGURE 2 - Floodway Schematic

5.0 INSURANCE APPLICATION

For flood insurance rating purposes, flood insurance zone designations are assigned to a community based on the results of the engineering analyses. These zones are as follows:

Zone AE

Zone AE is the flood insurance rate zone that corresponds to the 100-year floodplains that are determined in the Flood Insurance Study by detailed methods. Whole-foot base flood elevations derived from the detailed hydraulic analyses are shown at selected intervals within this zone.

Zone X

Zone X is the flood insurance rate zone that corresponds to areas outside the 500-year floodplain, areas within the 500-year floodplain, areas of 100-year flooding where average depths are less than 1 foot, areas of 100-year flooding where the contributing drainage area is less than 1 square mile, and areas protected from the 100-year flood by levees. No base flood elevations or depths are shown within this zone.

6.0 FLOOD INSURANCE RATE MAP

The Flood Insurance Rate Map is designed for flood insurance and floodplain management applications.

For flood insurance applications, the map designates flood insurance rate zones as described in Section 5.0 and, in the 100-year floodplains that were studied by detailed methods, shows selected whole-foot base flood elevations or average depths. Insurance agents use the zones and base flood elevations in conjunction with information on structures and their contents to assign premium rates for flood insurance policies.

BEST COPY AVAILABLE

For floodplain management applications, the map shows by tints, screens, and symbols the 100- and 500-year floodplains, the floodways, and the locations of selected cross sections used in the hydraulic analyses and floodway computations.

7.0 OTHER STUDIES

A Flood Insurance Study is in progress for the Unincorporated Areas of Tuscarawas County, Ohio (Reference 4) and is in agreement with this study.

Due to its more detailed analysis, this Flood Insurance Study supersedes the previously printed Flood Hazard Boundary Map for the Village of Strasburg, Tuscarawas County, Ohio (Reference 8).

8.0 LOCATION OF DATA

Information concerning the pertinent data used in the preparation of this study can be obtained by contacting the Natural and Technological Hazards Division, FEMA, 300 South Wacker Drive, Chicago, Illinois 60606.

9.0 REFERENCES AND BIBLIOGRAPHY

1. U.S. Department of Agriculture, Soil Conservation Service, Flood Plain Management Study Sugar Creek, South Fork of Sugar Creek, Brandywine Creek and Broad Run, Tuscarawas County, Ohio, March 1985.

2. U.S. Department of Commerce, Bureau of the Census, 1980 Census of Population, Number of Inhabitants, Ohio, Washington, D.C., February 1982.

3. U.S. Army Corps of Engineers, Huntington District, Flood Plain Information, Tuscarawas River and Adjacent Tributary Areas, Tuscarawas County, Ohio, Huntington, West Virginia, June 1973.

4. Federal Emergency Management Agency, Flood Insurance Study, Tuscarawas County, Unincorporated Areas, Ohio, in progress.

5. Beard, Leo, R., Statistical Methods in Hydrology, January 1962.

6. U.S. Geological Survey, 7.5 Minute Series Topographic Maps, Scale 1:24000, Contour Interval 20 feet: Strasburg, Ohio, 1961.

7. U.S. Department of Agriculture, Soil Conservation Service, Technical Release No. 61, WSP-2 Computer Program, May 1976.

8. U.S. Department of Housing and Urban Development, Federal Insurance Administration, Flood Hazard Boundary Map, Village of Strasburg, Tuscarawas County, Ohio, July 1976.

BEST COPY AVAILABLE

ELEVATION REFERENCE MARKS

REFERENCE MARK	FLOOD INSURANCE RATE MAP PANEL	ELEVATION (FEET NGVD)	DESCRIPTION OF LOCATION
1	0001	923.89	Tuscarawas County tablet set in northwest corner of north abutment of County Route 99 bridge over Sugar Creek

BEST COPY AVAILABLE



01P	FEDERAL EMERGENCY MANAGEMENT AGENCY **VILLAGE OF STRASBURG, OH** (TUSCARAWAS CO.)	**FLOOD PROFILES** **SUGAR CREEK**

BEST COPY AVAILABLE